

NFC-500S-UL / NFC-500SA-UL CONVENTIONAL PHOTOELECTRIC SMOKE DETECTOR

PRODUCT OVERVIEW

MODEL: NFC-500S-UL / NFC-500SA-UL

NEVERFIRE photoelectric smoke detector represent a significant advancement in conventional detection, incorporating three key features which are instant inspection, intelligence and installation ease.

Instant inspection. NFC-500S-UL / NFC-500SA-UL provides wide-angle red LED indicators for instant inspection of detector condition.

Intelligence. NFC-500S-UL / NFC-500SA-UL carry a number of intelligent features to simplify testing and maintenance Drift compensation smoothing algorithms to avoid false alarm.

Installation ease. NEVERFIRE smoke detector characterizes by installation ease with its plug-in design which allows an installer to pre-wire the bases included with the head. NFC-500S-UL / NFC-500SA-UL photoelectric smoke detector is standard sensitivity detector is recommended for most applications, It is designed to work with all conventional panels.

photoelectric smoke detector consists of an IR emitter and Photodiode receiver, the emitter send a very narrow pulsed ray which scattered if it collides with smoke particles inside the sampling chamber. the photodiode receiver detect some of scattered beams which initiate the fire signal to the panel.



NEVERFIRE APPROVALS		PRODUCT COMPLIANCE
ISO 9001:2015 CERTIFIED	CE QACE202401069	EN54-7

DESCRIPTION

NEVERFIRE smoke detectors are low profile and have dual LEDS with 360 degree visibility, they are flashing in standby state but in fire state, they light up continuously in red. All data is written on the detector with lasers so that it cannot be erased or changed at all.

NFC-500S-UL / NFC-500SA-UL photoelectric smoke detectors have been designed to EN54-7 and certified CE QACE20241069⁽¹⁾ which play a vital role in ensuring that NEVERFIRE products placed on the market of the world are safe. NEVERFIRE products certified ISO9001:2015⁽¹⁾ Quality management systems and requirements, which is global standard for trusted goods and services



(1) you can view & download these certificates from ASSS website www.asss-eg.com

©2025 ASSS com., The company reserves the right to change the specifications of the products at any time and without prior notice.

All information in this documents is given in good faith but ASSS com. Cannot be held Responsible for any imissions or errors. Printed in Egypt.

Issue: 001

Date: 2025/01/08

Page: 1 of 2

AL ALAMIA FOR SAFETY & SECURITY SYSTEMS COM. (ASSS)

Factory: 16C, south industrial Zone, 10th of Ramadan City, Sharkyia, Egypt.

Administration: No.6, 163 St, Behind the military hospital, El Maadi, Cairo, Egypt.

TEL.: +2 02 25249113

FAX.: +2 02 25281778

MOBILE: +2 01129277269

E-Mail: info@asss-eg.com

WWW.ASSS-EG.COM

ASSS FACTORY is the first manufacture for fire alarm system in Africa & middle east.

The com. established since 2011 located in cairo governorate while the factory located in Sharkyia governorate.



FIRE DETECTION SYSTEM

ISO9001

CE QACE202401069

NFC-500S-UL / NFC-500SA-UL CONVENTIONAL PHOTOELECTRIC SMOKE DETECTOR

FEATURES

- ✓ Superior performance and reliability.
- ✓ Infrared Scattering Technology.
- ✓ Remote alarm indicating LED output.
- ✓ Two-wire, plug-in conventional detection technology.
- ✓ Wide angle LED's visibility (dual red color indication).
- ✓ 4" mounting base detector.
- ✓ Compatible with all NEVERFIRE conventional bases.
- ✓ Simplified sensitivity measurement.
- ✓ Removable detector cover and chamber for easy cleaning.
- ✓ High signal-to-noise ratio and sensitivity stability are effective in a wide range of environmental conditions.
- ✓ Attractive new design.
- ✓ Meet EN54-7 Requirements.
- ✓ Low power consumption.
- ✓ Designed for Fast and easy installation.
- ✓ Compatible with most of fire alarm panels.

TECHNICAL SPECIFICATIONS

Model	NFC-500S-UL	NFC-500SA-UL
Operating Voltage	9~33V DC from fire alarm control panel IDC	
Standby current	40 μ A	
Surge current	170 μ A	
Alarm current	15 mA	
Startup time	10seconds	
Smoke Sensitivity	0.08 dB\m – 0.12dB\m	
Remote Output	15mA max. open collector	
Installation space	6m between each detector	

OPERATING CONDITION

Storage Temperature Range	-10°C to 50°C (14°F to 122°F)
Operating Temperature Range	0°C to 37°C (32°F to 98.6°F)
Operating Humidity Range	0%-95% Relative Humidity, non-condensing

MECHANICAL SPECIFICATIONS

Ingress Protection Rating	IP42	
Material	ABS Terminals: Iron Nickel plated - stainless Steel	ABS (Fire Proof Plastic) Terminals: Iron Nickel plated - stainless Steel
Color	White	
Diameter	100mm Dia.	
Height	55mm with base	
Weight	145g with base	
Packaging	90Unit/Carton	
Carton Dimensions	55*33*38cm	

WARRANTY

NEVERFIRE warrants that product from defects in design, materials and workshop during the warranty peroid ensuring customers' confidence in product quality and performance.

For comprehensive information, including installation guidelines and compatibility details, please consult NEVERFIRE Installation Manual or reach out to our technical support team. Anybody, including the agents, distributors or empolyees, is not in the position to amend the contents of this warranty.

©2025 ASSS com., The company reserves the right to change the specifications of the products at any time and without prior notice.

All information in this documents is given in good faith but ASSS com. Cannot be held Responsible for any imissions or errors. Printed in Egypt.

AL ALAMIA FOR SAFETY & SECURITY SYSTEMS COM. (ASSS)

Factory: 16C,south industrial Zone,10th of Ramadan City, Sharkyia, Egypt.

Administration: No.6, 163 St, Behind the military hospital, El Maadi, Cairo, Egypt.

TEL.: +2 02 25249113

FAX.: +2 02 25281778

MOBILE: +2 01129277269

E-Mail: info@asss-eg.com

WWW.ASSS-EG.COM

Issue: 001 Date: 2025/01/08 Page: 2 of 2
ASSS FACTORY is the first manufacture for fire alarm system in Africa & middle east.

The com. established since 2011 located in cairo governorate while the factory located in Sharkyia governorate.